

Mini enterprises

BLUE WAX

IT IS A HIGH GLOSS PASTE WAX OFFERING MULTIPLE AND EASY RELEASES, ELIMINATING THE USE OF PVA .BESIDES FIBRE MOLDS THIS WAX WORKS ON METAL AND WOODEN MOLDS/PATTERNS ALSO.

CONSUMPTION : 0.06 GRAMS PER SQ FOOT

APPLICATION : FOAM

INITIAL PROCEDURE: APPLY ONE COAT IN CIRCULAR CLOCKWISE MOTION, COAT THE EDGES AND CORNERS ONCE MORE CAREFULLY

DRYING TIME :15-20 MINUTES DEPENDING ON THE WEATHER

CONDITIONS

WIPE LIGHTLY WITH TERRY TOWEL TO GET EVENESS AND LITTLE SHINE

APPLY SECOND COAT IN CIRCULAR CLOCKWISE MOTION, COAT THE EDGES AND CORNERS ONCE MORE CAREFULLY

DRYING TIME :15-20 MINUTES DEPENDING ON THE WEATHER CONDITIONS

WIPE LIGHTLY WITH TERRY TOWEL TO GET EVENESS AND LITTLE SHINE

LEAVE THE MOLD FOR 30 MINUTES TO ALLOW THE WAX LAYER TO HARDEN

RELEASES: KEEP RELEASING PARTS TILL THE PULL GETS HARDER

Mini enterprises

SUBSEQUENT PROCEDURE

APPLY ONE COAT IN CIRCULAR CLOCKWISE MOTION,

COAT THE EDGES AND CORNERS ONE MORE CAREFULLY

DRYING TIME :15-20 MINUTES DEPENDING ON THE WEATHER
CONDITIONS

LEAVE THE MOLD FOR 15 MINUTES TO ALLOW THE WAX LAYER TO HARDEN

RELEASES: KEEP RELEASING PARTS TILL THE PULL GETS HARDER

REPEAT THE ABOVE STEP AGAIN

FOR SINGLE RELEASE WITH BLUE WAX

APPLY ONE COAT IN CIRCULAR CLOCKWISE MOTION,

COAT THE EDGES AND CORNERS ONCE MORE CAREFULLY

DRYING TIME : 5-7 MINUTES DEPENDING ON THE WEATHER
CONDITIONS

WIPE LIGHTLY WITH TERRY TOWEL TO GET EVENESS AND LITTLE SHINE

RELEASE: RELEASE 1 PART

for video demo pls go to this link:

<http://www.youtube.com/watch?v=MRfwTymx3tQ&feature=plcp>