

# Mini enterprises

## **MOLD MAINTENANCE**

( PLS SEE THE VIDEO)

- 1) REMOVE WAX AND PVA USING WATER EMERY
- 2) START WITH 220 GRIT
- 3) USE 320 GRIT NEXT
- 4) FINALLY USE 1000 GRIT

APPARATUS : VARIABLE SPEED POLISHER WITH WOOL PAD

## **COARSE CUTTING COMPOUND 1**

APPLICATION : 5 GMS PER SQ FEET

POLISHING SPEED: 0 TO MEDIUM

## **FINE CUTTING COMPOUND 2**

APPLICATION : 2 GMS PER SQ FEET

POLISHING SPEED: MEDIUM TO HIGH

# Mini enterprises

IF MORE GLOSS IS REQUIRED THEN USE

## **POLISHING COMPOUND HIGH GLOSS 3**

APPLICATION : 2 GMS PER SQ FEET

POLISHING SPEED MEDIUM TO HIGH

MICRO POLISHING COMPOUND CAN ALSO BE USED ON

GELCOAT LAMINATES TO GET VERY HIGH GLOSS AND

SMOOTH SURFACE AS DEMONSTRATED IN THE VIDEO

FOR ANY CLARIFICATIONS CONTACT AT :

+9216371849/+9212088485 OR MAIL: [minigrp@gmail.com](mailto:minigrp@gmail.com)

FOR A VIDEO DEMO PLS GO TO THE LINK :

<http://www.youtube.com/watch?v=Bp7KuJehY0Q&feature=plcp>